




## MODEL 7175



### Baseball/ Softball Scoreboard

This baseball/ softball scoreboard displays HOME and GUEST scores to 99, INNING to 9, and indicates BALL, STRIKE and OUT.

#### SCOREBOARD SPECIFICATIONS

**DIMENSIONS:** Height 4'0", Width 10'0", Depth 6" (1219mm, 3048mm, 152mm). Weight 150lb (55kg).

**POWER REQUIREMENTS:** 120VAC @ 1.7Amp, Max Power 200 W. 240VAC power available.  
Optional 12VDC battery to power scoreboard also available.

**CONSTRUCTION:** Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8.

**DIGITS & INDICATORS:** The nominal digit size is 18" (457mm) and 12" (305mm) high for Innings. All digits are 7-segment electromagnetic, light reflecting, and outdoor approved.

**CAPTIONS:** HOME and GUEST captions are 7-3/4" (197mm) high. INNING caption is 4" (101mm) high all other captions are 5" (127mm) high. Stripe is 1/2" (13mm) in width. Captions and stripe are white vinyl, applied directly to the face. Other caption colors are available upon request.

**CABINET FINISH:** All cabinets are finished with the highest UV protected powder coat in the industry to ensure minimal fading for the life of the scoreboard.



## 7175 PRODUCT SPECIFICATIONS (CONTINUED)

### **OPERATING TEMPERATURES:**

-22 to 122 degrees Fahrenheit (-30 to 50 degrees Celsius)  
Console: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius)

### **7175 CONTROL CONSOLE:**

Control console is housed in a durable stainless steel case. Console has a 40-character liquid crystal display to recall and verify information being displayed on the scoreboard. The control console maybe operated on 120VAC or an optional 12VDC battery. The standard power cord included with the control console is 6 feet long. Maximum power demand is 4 watts.

### **CONTROL CABLE:**

One-pair shielded twisted cable of 22AWG is required for communication from the control console to the scoreboard (cabled scoreboards only).

### **SERVICE ACCESS:**

All digit modules and electronics are serviced from the front of the scoreboard.

### **MOUNTING:**

The scoreboard is typically mounted on two vertical beams, minimum size of W6 x 15. Beams are not supplied by Eversan, Inc. Eversan, Inc. supplies four Z-brackets to mount the scoreboard to the beams.

### **GENERAL INFORMATION:**

Scoreboard is capable of scoring for two teams. 100% solid state electronics housed in an all aluminum cabinet. Scoreboard comes complete and ready to install. Mounting brackets are supplied. Specifications and pricing are subject to change without notice.

### **WARRANTY:**

Eversan, Inc. warranty scoreboard and control console for five years. Warranty includes cost of labor and parts when returned prepaid to Eversan, Inc. Eversan, Inc. will not pay for repairs made by anyone other than authorized factory personnel. Switches, connectors or cables are not covered under warranty.

### **OPTIONS (call for quotes):**

1. 2.4GHz spread spectrum radio control.
2. Logo/ sponsor panels.
3. Team name in place of HOME.
4. Electronic message display.
5. Durable carrying case for control console.
6. Team names on changeable panels.
7. 12V rechargeable battery for control console operation.
8. Protective netting.