



MODEL 933I



Multi-Sport Scoreboard

This multi-sport outdoor scoreboard displays SCORES to 99, PERIOD to 9, indicates TIME to 99:59, SHOTS to 99, SAVES to 99, CORNERS to 99, and FOULS to 99 for both home and guest. Striping on the scoreboard is standard.

SCOREBOARD SPECIFICATIONS

DIMENSIONS: Height 9', Width 34', Depth 6" (2743mm, 10363mm, 152mm). Weight 480lb (218kg).

POWER REQUIREMENTS: 120VAC @ 8Amp, Max Power 960 W. 240VAC power available.

CONSTRUCTION: Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8.

DIGITS & INDICATORS: The nominal digit size for the HOME and GUEST score, TIME, and PERIOD digits are 24" (609mm) high. Remaining digits are 18" (457mm) high. All digits are 7-Segment Ultra bright outdoor LED. Digits can be dimmed for night viewing. Digit colors are red or amber.

CAPTIONS: HOME and GUEST caption is 10" (254mm) high. All other captions are 8" (203mm) high. Stripe is 1" (25mm) in width. Captions, colon, and stripe are white vinyl, applied directly to the display face. Other caption colors are available upon request.

CABINET FINISH: All cabinets are finished with the highest UV protected powder coat in the industry to ensure minimal fading for the life of the scoreboard.



-9331 PRODUCT SPECIFICATIONS (CONTINUED)

OPERATING TEMPERATURES:

-22 to 122 degrees Fahrenheit (-30 to 50 degrees Celsius)

Console: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius)

9331 CONTROL CONSOLE:

Control console is housed in a durable stainless steel case. Console has a 40-character liquid crystal display to recall and verify information being displayed on the scoreboard. The control console may be operated on 120VAC or an optional 12VDC battery. The standard power cord included with the control console is 6 feet long. Maximum power demand is 4 watts.

CONTROL CABLE:

One-pair shielded twisted cable of 22AWG is required for communication from the control console to the scoreboard (cabled scoreboards only).

SERVICE ACCESS:

All LED modules and electronics are serviced from the front of the scoreboard.

MOUNTING:

The scoreboard is typically mounted on three vertical beams, minimum size of W10 x 30, 9' on center. Beams are not supplied by Eversan, Inc. Eversan, Inc. supplies six Z-brackets to mount the scoreboard to the beams.

GENERAL INFORMATION:

Scoreboard is capable of timing and scoring for two teams. 100% solid state electronics housed in an all aluminum cabinet. Scoreboard comes complete and ready to install. Four mounting brackets are supplied. Specifications and pricing are subject to change without notice.

WARRANTY:

Eversan, Inc. warranty scoreboard and control console for five years. Warranty includes cost of labor and parts when returned prepaid to Eversan, Inc. Eversan, Inc. will not pay for repairs made by anyone other than authorized factory personnel. Switches, connectors or cables are not covered under warranty.

OPTIONS (call for quotes):

1. 2.4GHz spread spectrum radio control.
2. Logo/ sponsor panels.
3. Team name in place of HOME.
4. Electronic message display.
5. Durable carrying case for control console.
6. Team names on changeable panels.
7. 12V rechargeable battery for control console operation.
8. Protective netting.
9. Horn
10. Reversible PERIOD and HALF caption panel.