




# MODEL 9364-100



## Football Scoreboard & Timer

This football scoreboard displays game time to 99:59 in track mode time is displayed to 99:59.99, HOME and GUEST scores to 99, T.O.L. (time outs left), DOWN, TO GO, BALL ON and QTR (quarter). A football indicator shows possession. All scoreboards come with striping.

## SCOREBOARD SPECIFICATIONS

**DIMENSIONS:** Height 10'0", Width 32'0", Depth 6" (3048mm, 9754mm, 152mm). Weight 700lb (318kg)

**POWER REQUIREMENT:** 120VAC @ 4Amp, Max Power 480 W. 240VAC power available.

**CONSTRUCTION:** Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8.

**DIGITS & INDICATORS:** Clock digits have a nominal size of 30" (762mm) high. T.O.L. digits have a nominal size of 18" (457mm) high. All other digits have a nominal size of 24" (610mm). All digits are 7-segment Ultra bright outdoor LED. Digits and indicators can be dimmed for night viewing. Digit colors are red or amber.

**CAPTIONS:** HOME and GUEST captions are 15" (381mm) high. All other captions are 12" (305mm) high. Stripe is 1" (25mm) in width. Captions and stripe are white vinyl, applied directly to the face. Other caption colors are available upon request.

**CABINET FINISH:** All cabinets are finished with the highest UV protected powder coat in the industry to ensure minimal fading for the life of the scoreboard.

**OPERATING TEMPERATURES:** -22 to 122 degrees Fahrenheit (-30 to 50 degrees Celsius). Console: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius).



## **9364-100 PRODUCT SPECIFICATIONS (CONTINUED)**

### **9364-100 CONTROL CONSOLE:**

Control console is housed in a durable stainless steel case. Console has a 40-character liquid crystal display to recall and verify information being displayed on the scoreboard. The control console may be operated on 120VAC or an optional 12VDC battery. The standard power cord included with the control console is 6 feet long. Maximum power demand is 4 watts.

### **CONTROL CABLE:**

One-pair shielded twisted cable of 22AWG is required for communication from the control console to the scoreboard (cabled scoreboards only).

### **SERVICE ACCESS:**

All LED modules and electronics are serviced from the front of the scoreboard.

### **MOUNTING:**

The scoreboard is typically mounted on three vertical beams, minimum size of W12 x 30, 10'-6" apart on center. Beams are not supplied by Eversan, Inc. Eversan, Inc. supplies six Z-brackets to mount the scoreboard to the beams.

### **GENERAL INFORMATION:**

Scoreboard is capable of scoring for two teams and keeping time to seconds. 100% solid state electronics housed in an all aluminum cabinet. Scoreboard ships in four sections and includes hardware to assemble and mount on three beams. Mounting brackets are supplied. Specifications and pricing are subject to change without notice.

### **WARRANTY:**

Eversan, Inc. warranty scoreboard and control console for five years. Warranty includes cost of labor and parts when returned prepaid to Eversan, Inc. Eversan, Inc. will not pay for repairs made by anyone other than authorized factory personnel. Switches, connectors or cables are not covered under warranty.

### **OPTIONS (call for quotes):**

1. 2.4GHz spread spectrum radio control.
2. Horn
3. Logo/ sponsor panels.
4. Team name in place of HOME.
5. Electronic message display.
6. Durable carrying case for control console.
7. Team names on changeable panels.
8. 12V rechargeable battery for control console operation.
9. Protective netting.