



MODEL 9685 PORTABLE OUTDOOR HOCKEY SCOREBOARD



This, full size, outdoor hockey scoreboard shows HOME and GUEST scores to 99, PERIOD to 9, and TIME to 99:59. The penalty display boards show HOME and GUEST PLAYERS PENALTY TIME to 9:59 and PLAYER to 99.

SCOREBOARD SPECIFICATIONS

DIMENSIONS: Height 30", Width 13', Depth 6" (762mm, 3962mm, 152mm). Weight 120lb (150kg)

POWER REQUIREMENT: 120VAC @ 6Amp, Max Power 720W. 240VAC power available.
Optional portable power pack operation available.

CONSTRUCTION: Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8.

DIGITS & INDICATORS: The nominal digit size is 8" (152mm) high. All digits are 7-segment Ultra bright outdoor LED. Digits can be dimmed for night viewing. Digit colors are red or amber.

CAPTIONS: HOME and GUEST captions are 4.5" (114mm) high. All other captions are 4" (102mm) high. Stripe is 1/2" (12mm) in width. Captions and stripe are white vinyl, applied directly to the face. Other caption colors are available upon request.

CABINET FINISH: All cabinets are finished with the highest UV protected powder coat in the industry to ensure minimal fading for the life of the scoreboard. All digits have a nominal size of 8" (mm) high. All digits are 7-segment ultra bright outdoor LED. Digits can be dimmed for night viewing. Digit colors are red or amber.

OPERATING TEMPERATURES: -22 to 122 degrees Fahrenheit (-30 to 50 degrees Celsius). Console:
32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius).



9685 PRODUCT SPECIFICATIONS (CONTINUED)

9685 CONTROL CONSOLE:

Control console is housed in a durable stainless steel case. Console has a 40-character liquid crystal display to recall and verify information being displayed on the scoreboard. The control console may be operated on 120VAC or an optional 12VDC battery. The standard power cord included with the control console is 6 feet long. Maximum power demand is 4 watts.

CONTROL CABLE:

One-pair shielded twisted cable of 22AWG is required for communication from the control console to the scoreboard (cabled scoreboards only).

SERVICE ACCESS:

All digit modules and electronics are serviced from the front of the scoreboard.

MOUNTING:

The scoreboard is typically mounted on two vertical beams, minimum size of W10 x 15, 9' apart on center. Beams are not supplied by Eversan, Inc. Eversan, Inc. has an optional installation kit available to assist in mounting to vertical beams.

GENERAL INFORMATION:

Scoreboard is capable of scoring and timing for two teams. 100% solid state electronics housed in an all aluminum cabinet. Scoreboard ships in three sections. Specifications and pricing are subject to change without notice.

WARRANTY:

Eversan, Inc. warranty scoreboard and control console for five years. Warranty includes cost of labor and parts when returned prepaid to Eversan, Inc. Eversan, Inc. will not pay for repairs made by anyone other than authorized factory personnel. Switches, connectors or cables are not covered under warranty.

OPTIONS (call for quotes):

1. 2.4GHz spread spectrum radio control.
2. Horn
3. Logo/ sponsor panels.
4. Team name in place of HOME.
5. Electronic message display.
6. Durable carrying case for control console.
7. Installation kit.
8. Rechargeable power pack for control console and scoreboard operation.
9. Protective netting.