



MODEL 9116



Baseball/Softball Scoreboard

This baseball/softball scoreboard displays HOME and GUEST scores and PITCH COUNTS to 99, INNING to 9, and indicated BALL, STRIKE, and OUT.

SCOREBOARD SPECIFICATIONS

DIMENSIONS: Height 3'0", Width 7'0", Depth 6" (915mm, 2133mm, 152mm). Weight 85lb (39kg)

POWER REQUIREMENT: 120VAC @ 1.7 Amp, Max Power 200 W. 240VAC power available.

CONSTRUCTION: Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8.

DIGITS & INDICATORS: The score and inning digit size is 11" (280mm) high, pitch count digit size is 8" (203mm) high. All digits are 7-segment Ultra bright outdoor LED. Digits and indicators can be dimmed for night viewing. Digit colors are red or amber.

CAPTIONS: HOME and GUEST captions are 5" (127mm) high. INNING and P.C. Are 3.5" (89mm). All other captions are 4" (102mm) high. Stripe is 1/2" (13mm) in width. Captions and stripes are white vinyl, applied directly to the face. Other caption colors are available upon request.

CABINET FINISH: All cabinets are finished with the highest UV protected powder coat in the industry to ensure minimal fading for the life of the scoreboard.

OPERATING TEMPERATURES: -22 to 122 degrees Fahrenheit (-30 to 50 degrees Celsius).
Console: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius).



9116 PRODUCT SPECIFICATIONS (CONTINUED)

9116 CONTROL CONSOLE:

Control console is housed in a durable stainless steel case. Console has a 40-character liquid crystal display to recall and verify information being displayed on the scoreboard. The control console may be operated on 120VAC or an optional 12VDC battery. The standard power cord included with the control console is 6 feet long. Maximum power demand is 4 watts.

CONTROL CABLE:

One-pair shielded twisted cable of 22AWG is required for communication from the control console to the scoreboard (cabled scoreboards only).

SERVICE ACCESS:

All LED modules and electronics are serviced from the front of the scoreboard.

GENERAL INFORMATION:

Scoreboard is capable of scoring for two teams. 100% solid state electronics housed in an all aluminum cabinet. Scoreboard comes complete and ready to install. Mounting brackets are supplied. Specifications and pricing are subject to change without notice.

WARRANTY:

Eversan, Inc. warranty scoreboard and control console for five years. Warranty includes cost of labor and parts when returned prepaid to Eversan, Inc. Eversan, Inc. will not pay for repairs made by anyone other than authorized factory personnel. Switches, connectors, and cables are not covered under warranty.

OPTIONS (call for quotes):

1. 2.4GHz spread spectrum radio control.
2. Horn
3. Logo/ sponsor panels.
4. Electronic message display.
5. Durable carrying case for control console.
6. 12V rechargeable battery for control console operation.
7. 600 Watt Rechargeable Battery Pack