



This delay of game timer comes with two displays that can count down from 0-99 and may be used with any style of the outdoor scoreboard.

## PRODUCT SPECIFICATIONS

**DIMENSIONS:** Height 3'0", Width 4'0", Depth 6" (914mm, 1219mm, 152mm)

POWER REQUIREMENTS: 120VAC @ 1.0 Amp, Max Power 120W. 240VAC power available.

**CONSTRUCTION:** Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8.

**DIGITS:** The nominal digit size is 30" (762mm) high. Digit color is red or amber.

**DISPLAY COLOR:** Cabinet is black with a white stripe. The white stripe is a white vinyl, applied directly to the display face. Other colors are available upon request.

**OPERATING TEMPERATURES:** Scoreboard: -22 to 122 degrees Fahrenheit (-30 to 50 degree Celsius). Control Console 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius).

**9330 CONTROL CONSOLE:** Control console housed in a durable aluminum case. No power required at the console (cabled systems only).

**CONTROL CABLE:** Four-conductor shielded 22AWG is required for communication from the console to each display (cabled systems only).

**SERVICE ACCESS:** All LED modules and electronics are serviced from the front of the display.

**GENERAL INFORMATION:** Specifications and pricing are subject to change without notice.

**WARRANTY:** Eversan, Inc. warranty scoreboard and console for five years.

**OPTIONS:** 2.4GHz spread spectrum radio control.