



MODEL 9342-AFP



Football Scoreboard & Timer

This football practice timer displays PERIOD to 99 and TIME to 99:99.
All scoreboards come with striping.

SCOREBOARD SPECIFICATIONS

DIMENSIONS: Height 26", Width 7', Depth 6" (660mm, 2134mm, 152mm). Weight 2000lb (998kg)

POWER REQUIREMENT: 120VAC @ 4Amp, Max Power 480 W. 240VAC power available.

CONSTRUCTION: Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8.

DIGITS & INDICATORS: All digits have a nominal size of 11" (279 mm). All digits are 7-segment Ultra bright outdoor LED. Digits and indicators can be dimmed for night viewing. Digit colors are red or amber.

CAPTIONS: All captions are 6" (152 mm) high. Stripe is 1" (25mm) in width. Captions and stripe are white vinyl, applied directly to the face. Other caption colors are available upon request.

CABINET FINISH: All cabinets are finished with the highest UV protected powder coat in the industry to ensure minimal fading for the life of the scoreboard.

OPERATING TEMPERATURES: -22 to 122 degrees Fahrenheit (-30 to 50 degrees Celsius).
Console: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius).

9342-AFP CONTROL CONSOLE:

Control console is housed in a durable stainless steel case. Console has a 40-character liquid crystal display to recall and verify information being displayed on the scoreboard. The control console maybe operated on 120VAC or an optional 12VDC battery. The standard power cord included with the control console is 6 feet long. Maximum power demand is 4 watts.

CONTROL CABLE:

One-pair shielded twisted cable of 22AWG is required for communication from the control console to the scoreboard (cabled scoreboards only).



9342-AFP PRODUCT SPECIFICATIONS (CONTINUED)

SERVICE ACCESS:

All LED modules and electronics are serviced from the front of the scoreboard.

GENERAL INFORMATION:

Scoreboard is capable of timing entire practices and/or workouts. Period lengths can be pre-programmed into the unit. Rest periods, between workouts can also be adjusted to better fit particular situations. 100% solid state electronics housed in an all aluminum cabinet. Specifications and pricing are subject to change without notice.

WARRANTY:

Eversan, Inc. warranty timer and control console for five years. Warranty includes cost of labor and parts when returned prepaid to Eversan, Inc. Eversan, Inc. will not pay for repairs made by anyone other than authorized factory personnel. Switches, connectors or cables are not covered under warranty.

OPTIONS (call for quotes):

1. 2.4GHz spread spectrum radio control.
2. Horn
3. Logo/ sponsor panels.
4. Durable carrying case for control console.
5. 12V rechargeable battery for control console operation.