



# PORTABLE L.E.D. FOOTBALL SCOREBOARD

This football scoreboard displays game time to 99:59, HOME and GUEST scores to 99, DOWN, TO GO, BALL ON and QTR (quarter). All scoreboards come with striping.

# SCOREBOARD SPECIFICATIONS

**DIMENSIONS:** Height 45", Width 48", Depth 3" (1143mm, 1219mm, 76mm). Weight 60lb (27 kg)

**POWER REQUIREMENT:** 120VAC @ 1Amp, Max Power 120 W. 240VAC power available. Optional 12VDC battery operation available.

**CONSTRUCTION:** Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8.

**DIGITS & INDICATORS:** The nominal digit size is 8" (203mm) high. All digits are 7-segment Ultra bright outdoor LED.Digits can be dimmed for night viewing. Digit colors are red or amber.

**CAPTIONS:** HOME and GUEST captions are 4" (102mm) high. All other captions are 3.5" (89mm) high. Stripe is 1/2" (13mm) in width. Captions and stripe are white vinyl, applied directly to the face. Other caption colors are available upon request.

**CABINET FINISH:** All cabinets are finished with the highest UV protected powder coat in the industry to ensure minimal fading for the life of the scoreboard.

EVERSAN, INC. • 34 Main Street, Whitesboro, NY 13492 • 1-800-383-6060 Fax: 315-736-4058 www.eversan.com



**OPERATING TEMPERATURES:** -22 to 122 degrees Fahrenheit (-30 to 50 degrees Celsius). Console: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius).

## 9600 CONTROL CONSOLE:

Control console is housed in a durable stainless steel case. Console has a 40-character liquid crystal display to recall and verify information being displayed on the scoreboard. The control console maybe operated on 120VAC or an optional 12VDC battery. The standard power cord included with the control console is 6 feet long. Maximum power demand is 4 watts.

#### CONTROL CABLE:

One-pair shielded twisted cable of 22AWG is required for communication from the control console to the scoreboard (cabled scoreboards only).

#### SERVICE ACCESS:

All digit modules and electronics are serviced from the front of the scoreboard.

#### **MOUNTING:**

The scoreboard is portable and can be hung from its carrying handles. A wheel cart is available to enable the use of the scoreboard in multiple locations.

#### **GENERAL INFORMATION:**

Scoreboard is capable of scoring for two teams. 100% solid state electronics housed in an all aluminum cabinet. Scoreboard ships in one section. Specifications and pricing are subject to change without notice.

#### WARRANTY:

Eversan, Inc. warranty scoreboard and control console for five years. Warranty includes cost of labor and parts when returned prepaid to Eversan, Inc. Eversan, Inc. will not pay for repairs made by anyone other than authorized factory personnel. Switches, connectors or cables are not covered under warranty.

## **OPTIONS** (call for quotes):

- 1. 2.4GHz spread spectrum radio control.
- 2. Horn
- 3. Logo/ sponsor panels.
- 4. Team name in place of HOME.
- 5. Electronic message display.
- 6. Durable carrying case for control console.
- 7. Team names on changeable panels.
- 8. 12V rechargeable battery for control console and scoreboard operation.
- 9. Protective netting.
- 10. Wheel Cart for easy maneuverability.