



MODEL 6720



Shot Clock System with Game Time

Indoor/Outdoor shot clocks featuring a 00-99 second programmable Shot Clock Timer along with 00-99 minute and 00-59 second timing for Game Clock.

SHOT CLOCK SPECIFICATIONS

DIMENSIONS: Height 31 1/2", Width 31", Depth 5 1/2" (800mm, 787mm, 140mm). Weight 25lb (11kg)

POWER REQUIREMENT: 120VAC @ .75 Amps, Max Power 75W. 240VAC power available.

CONSTRUCTION: Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8. Face and back plate depth is .063" aluminum, frame depth is .080" aluminum.

DIGITS & INDICATORS: The shot clock digit size is 15" (381mm) high and the game time digit size is 8" (203mm) high. All digits are 7-segment Ultra bright indoor/outdoor LED. Digits and indicators can be dimmed for night viewing. Digit colors are red or amber.

CABINET FINISH: All cabinets are finished with the highest UV protected powder coat in the industry to ensure minimal fading for the life of the scoreboard.



6720 Specifications Continued

OPERATING TEMPERATURE: -22 to 122 degrees Fahrenheit (-30 to 50 degrees Celsius).
Console: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius).

6720 CONTROL CONSOLE: 6720 Shot Clocks may be controlled by an existing 6700 series basketball scoreboard control console or a control console can be purchased to operate the shot clocks independently. Control console is housed in a durable stainless steel case. Console has a 40-character liquid crystal display to recall and verify information being displayed on the scoreboard. The control console maybe operated on 120VAC or an optional 12VDC battery. The standard power cord included with the control console is 6 feet long. Maximum power demand is 4 watts.

CONTROL CABLE: One-pair (2-conductor) shielded twisted cable of 22AWG is required for communication from the control console to the scoreboard (cabled scoreboards only).

SERVICE ACCESS: All LED modules and electronics are serviced from the front of the shot clocks.

GENERAL INFORMATION: Shot clocks have a 00-99 second programmable Shot Clock Timer along with a 00-99 minutes and 00-59 second timing for Game Clock. 100% solid state electronics housed in an all aluminum cabinet. Shot clocks come complete and ready to install. Specifications and pricing are subject to change without notice.

WARRANTY:

Eversan, Inc. warranty shot clocks for one year. Warranty includes cost of labor and parts when returned prepaid to Eversan, Inc. Eversan, Inc. will not pay for repairs made by anyone other than authorized factory personnel. Switches, connectors, and cables are not covered under warranty.

OPTIONS (call for quotes):

1. 2.4GHz spread spectrum radio control (wireless)
2. Horn
3. Dedicated Control Console
4. Durable carrying case for control console.
5. 12V rechargeable battery for control console operation.