


EVERSAN

MODEL 9012



Player Penalty Display

This player penalty scoreboard displays PLAYER number to 99 and PENALTY time to 9:59, for two teams. The scoreboard will operate as a standalone unit or can be added to any 25' football or soccer scoreboard to score lacrosse or field hockey. Scoreboard comes with an area for an optional logo/ sponsor

SCOREBOARD SPECIFICATIONS

DIMENSIONS: Height 5'0", Width 25'0", Depth 6" (1524mm, 7620mm, 152mm). Weight 480 lb (218 kg)

POWER REQUIREMENT: 120VAC @ 4Amp, Max Power 480 W. 240VAC power available.

CONSTRUCTION: Aluminum alloy 5052, conforms to Federal specification QQ-A-250/8.

DIGITS & INDICATORS: The nominal digit size of all numbers is 18" (457mm) high.
All digits are 7-segment Ultra bright outdoor LED. Digits and
can be dimmed for night viewing. Digit colors are red or amber.

CAPTIONS: All captions are 9" (229mm) high. Stripe is 1" (25mm) in width. Captions and stripe
are white vinyl, applied directly to the face. Other caption colors are
available upon request.

CABINET FINISH: All cabinets are finished with the highest UV protected powder coat in the industry
to ensure minimal fading for the life of the scoreboard.

OPERATING TEMPERATURES: -22 to 122 degrees Fahrenheit (-30 to 50 degrees Celsius). Console:
32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius).



9012 PRODUCT SPECIFICATIONS (CONTINUED)

9012 CONTROL CONSOLE:

Control console is housed in a durable stainless steel case. Console has a 40-character liquid crystal display to recall and verify information being displayed on the scoreboard. The control console maybe operated on 120VAC or an optional 12VDC battery. The standard power cord included with the control console is 6 feet long. Maximum power demand is 4 watts.

CONTROL CABLE:

One-pair shielded twisted cable of 22AWG is required for communication from the control console to the scoreboard (cabled scoreboards only).

SERVICE ACCESS:

All LED modules and electronics are serviced from the front of the scoreboard.

MOUNTING:

The scoreboard is typically mounted on three vertical beams, minimum size of W10 x 15, 10' apart on center. Beams are not supplied by Eversan, Inc. Eversan, Inc. supplies six Z-brackets to mount the scoreboard to the beams.

GENERAL INFORMATION:

Scoreboard is capable of providing player and penalty information for two teams. 100% solid state electronics housed in an all aluminum cabinet. Scoreboard ships in two sections and includes hardware to assemble and mount on three beams. Mounting brackets are supplied. Specifications and pricing are subject to change without notice.

WARRANTY:

Eversan, Inc. warranty scoreboard and control console for five years. Warranty includes cost of labor and parts when returned prepaid to Eversan, Inc. Eversan, Inc. will not pay for repairs made by anyone other than authorized factory personnel. Switches, connectors or cables are not covered under warranty.

OPTIONS (call for quotes):

1. 2.4GHz spread spectrum radio control.
2. Logo/ sponsor panels.
3. Durable carrying case for control console.
4. 12V rechargeable battery for control console operation.
5. Protective netting.