

EVERSAN

L.E.D. LIGHT STRIP INSTALLATION DIAGRAM

1. MOUNT TOP HORIZONTAL LIGHT STRIP IN POSITION ON THE BACK BOARD USING #8 SELF TAPPING SCREWS TO SECURE IT TO THE FRAME OF THE BACKBOARD. THE 6FT CABLE SHOULD REACH THE SHOTCLOCK MOUNTED ABOVE THE BACKBOARD.

2. SECURE THE TWO VERTICLE STRIPS TO THE HORIZONTALSTRIP USING A 6-32 SCREW. CNNECT THE FOUR PIN INTER CONNECT ONTHE UPPER LEFT HAND CORNER.

3. SECURE THE BOTTOM HORIZONTAL STRIP TO BOTH THE BACKBOARD AND VERTICLE STRIPS. BE SURE TO CONNECT THE FOUR PIN CONNECTORS IN EACH CORNER.

4. IF THE TOP AND BOTTOM STRIPS ARE TO LONG FOR YOUR BACKBOARD A FIELD MODIFICATION CAN BE APPLIED, CUT ENOUGH OFF EACH STRIP, BUT NOT ENOUGH TO INTERFERE WITH THE ELECTRICAL PARTS OF THE STRIP, TO MAKE THE PIECES FIT.

5. CONNECT THE FOUR PIN CONNECTOR TO THE SHOTCLOCK DISPLAY AND TEST.

